




RCB-JFB 自润滑翻边轴承 Self-lubricating flanging bearing



材质	高力黄铜+石墨
Material	CuZn25Al6Mn4+ Graphite



单位unit:mm

IDE7 (内径)	ODr6 (外径)	F	ℓ_1 -0.10	L -0.10 -0.30												
				15	20	25	30	35	40	50	60	80	100			
10	$14^{+0.040}_{+0.025}$	22	2	1015F	1020F											
12	18	$25^{+0.034}_{+0.023}$	3	1215F	1220F											
13	19	26		1315F	1320F											
14	$20^{+0.050}_{+0.032}$	27		1415F	1420F											
15	21	$28^{+0.041}_{+0.028}$		1515F	1520F	1525F	1530F									
16	22	29	1615F	1620F	1625F	1630F										
20	30	40	2015F	2020F	2025F	2030F		2040F								
25	$35^{+0.061}_{+0.040}$	45	2515F	2520F	2525F	2530F		2540F								
30	40	50		3020F	3025F	3030F	3035F	3040F	3050F							
31.5	40	$50^{+0.050}_{+0.034}$	5	3120F			3135F									
35	45	60			3520F		3530F		3540F	3550F						
40	$50^{+0.075}_{+0.050}$	65			4020F		4030F		4040F	4050F						
45	55	70					4530F		4540F	4550F	4560F					
50	60	$75^{+0.060}_{+0.041}$	7.5			5030F		5040F	5050F	5060F						
55	65	80							5540F		5560F					
60	75	$90^{+0.062}_{+0.043}$							6040F	6050F			6080F			
63	75	85											6367F			
70	$85^{+0.090}_{+0.060}$	105	10						7050F			7080F				
75	90	$110^{+0.073}_{+0.051}$									7560F					
80	100	120										8060F	8080F	80100F		
90	110	$130^{+0.076}_{+0.054}$									9060F	9080F				
100	$120^{+0.107}_{+0.072}$	150										10080F	100100F			
120	140	$170^{+0.088}_{+0.063}$										12080F	120100F			